

## **Keeping South Florida Healthy** & Fit for over 25 Years!

### **IC5 INDOOR CYCLE**



# WATTRATE® LCD CONSOLE













POWER MEASUREMENT (WATT)

COMPUTER POWER SUPPLY



WattRate® Power Meter (DIN EN ISO 20957-10)

WattRate® LCD Computer

**Batteries** 

# IC5 INDOOR CYCLE SPECIFICATIONS



### TRAINING INTENSITY GUIDE Coach By Color® (user) Bluetooth and ANT+ CONNECT TECHNOLOGY WORKOUT TRACKING ICG Training App RESISTANCE SYSTEM Magnetic Push (EN-957-10) **EMERGENCY STOP** FLYWHEEL Rear, aluminum, evenly-weighted DRIVETRAIN Poly-V belt DRIVETRAIN GEAR RATIO 1:10 FRAME COLOR Matte slate FRAME MATERIAL Steel

COMPUTER

Full fram SHROUDS/GUARDS FRAME DESIGN Off-set ADJUSTMENT TYPE Dials & levers Aluminum, pin-to-lock adjustment **POSTS & SLIDERS** USER ASSIST ADJUSTMENTS Handlebar assisted 155mm / 6.1" Q FACTOR CrMo 172,5mm / 6.79" CRANK TYPE Dual-sided SPD & toe cage PEDAL TYPE HANDLEBAR Ergo-formed, multi position, soft PVC HANDLEBAR ADJUSTMENTS Vertical & horizontal Unisex padded sport saddle SADDLE SADDLE ADJUSTMENTS Vertical & horizontal WATER BOTTLE HOLDER Dual, integrated on handlebar FRAME STABILIZER BARS Oversized, hidden bolts & fixings PROTECTION & STRETCH PLATES Molded form-fit with stretch plate MAX USER WEIGHT 150 kg / 330 lbs

51 kg / 112 lbs

3 years\*

### \*WARRANTY

| 5 YEARS  | Frame construction and welding  |
|--|---|
| 3 YEARS  | Powder coating, handlebar & seat post assembly (aluminum parts & PVC coating), belt drive system, bottom bracket, flywheel, hub, cranks, pedals, insert sleeves, bowden cables, brake system, gas spring, lever assembly, levelling feet, shroud & top covers |
| 1 YEAR   | $Saddle\ construction\ (stitching\ \&\ saddle\ deck\ not\ included),\ IC6\ electronics\ (console,\ cable\ harness,\ PCBs\ \&\ sensors,\ generator),\ lithium\ polymer\ battery$   |
| WEAR ITEMS EXCLUDED FROM WARRANTY: PEDAL STRAPS, PEDAL BINDING SYSTEM SADDLE SURFACE |   |





ASSEMBLED WEIGHT

LEVELING FEET TRANSPORT WHEELS WARRANTY (PARTS)

ASSEMBLED DIMENSIONS



L132xW52xH120cm / 52"x20.5"x47.2"